



## Polar Flux Remover

- Cleans heavy, aged flux
- Removes polar & ionic activators
- Fast, extra-strength cleaning
- Cleans & minimizes white residues
- High purity, dries residue-free
- Excellent silicone remover
- TriggerGrip™ cleaning system compatible

### Product Information

Polar Flux Remover is an economical flux remover for cleaning aged and heavy baked-on fluxes. The residue-free formula works on R, RA, RMA, and No-Clean fluxes for both tin/lead solders and high temperature lead-free solders. It quickly penetrates and dissolves excess flux and removes ionic and non-ionic activators that cause white residues. It dries residue free.

This extra-strength flux remover cleans all types of flux, pastes, inks, finger prints, oxides, oils, and grease. It also effectively dissolves many adhesives and silicone fluids commonly found on electronic assemblies. Use Polar Flux Remover on printed circuit boards, FR-4, components, connectors, cables, and mechanical assemblies. Test before use on plastics.

*AVAILABILITY: Stocked by MicroCare distributors world-wide. Contact MicroCare for a distributor near you. For more information contact MicroCare directly or visit [www.MicroCare.com](http://www.MicroCare.com).*

### Discover Perfectly Clean [www.MicroCare.com](http://www.MicroCare.com)

**MicroCare Corporation**  
595 John Downey Drive  
New Britain, CT 06051 USA  
CAGE: OATV9  
Tel: +1 860 827 0626  
Toll Free: 1 800 638 0125  
Email: TechSupport@MicroCare.com

**MicroCare Europe BVBA**  
Vekestraat 29 B11  
Industriezone 't Sas  
1910 Kampenhout, Belgium  
Tel: +32 2 251 95 05  
Email: EuroSales@MicroCare.com

**MicroCare U.K. Ltd**  
Seven Hills Business Park,  
Morley,  
Leeds, West Yorkshire, UK  
LS27 8AT  
Tel: +44 (0) 113 2501008  
mceurope@microcare.com

**MicroCare Asia Pte Ltd**  
102E Pasir Panjang Road  
#03-01 Citilink Warehouse Complex  
Singapore 118529  
Tel: +65 6271 0182  
Email: TechSupport@MicroCare.sg

Technical Details and Cleaning Data	
Boiling Point	55 °C / 131 °F
Chemical Family	Organic Solvent
Cleaning Strength (KB value)	72
Evaporation Rate	Slow
Odor	Acetone
Percent Volatile	100%
Specific Gravity	0.75 g / ml
Health, Safety and Environmental Data	
Flammable	Yes
RoHS and WEEE Compliant	Yes
REACH Compliant	Yes*
VOC Content	190 g / L
SNAP-Approved	Yes
GHS / HCS Pictogram	
Packaging	
Aerosol - 10 oz / 300 g	MCC-PFR10A
Minipail - 6 lb / 2.72 kg	MCC-PFRG
Pail - 32 lb / 14.5kg	MCC-PFRP
Drum - 330 lb / 149.7 kg	MCC-PFRD
TriggerGrip™ Compatible	Yes
Aerosol Packaging	12 cans / box
Shelf Life	Unlimited
Recycle	

\*Contact MicroCare for specific details

