



B43390 Aspirapolvere esd

TRULY VERSATILE EPA VACUUM CLEANER / BLOWER WITH ADVANCED CLEANROOM HI-FILTRATION SYSTEM FOR FACTORY CONTRACT CLEANING AND HARD TO REACH DUST & DEBRIS FROM ESD SENSITIVE ELECTRONIC EQUIPMENT, ASSEMBLY LINES, R&D AREA'S AND IN FIELD-SERVICE.

- ✓ CONTROLLED SOFT (SR : 10E7 - 10E8 OHMS/SQ.) ESD-SAFE STATIC DISCHARGE FROM HOUSING AND VACUUM NOZZLES TO EARTH POWER OUTLET.
- ✓ EPA COMPLIANT TO IEC 61340-5-1
- ✓ EEC MADE TOP QUALITY ELECTRICAL & ELECTRONIC COMPONENTS FOR UTMOST RELIABILITY AND GLOBAL USE.
- ✓ UNIT OVERHEATING PROTECTED & RFI/EMC FILTER EQUIPPED.
- ✓ EASY TO MOVE AROUND THANKS TO LOW MOTOR MOUNT, WHEEL WELL PROTECTED CASTOR AND ROBUST REAR WHEELS.
- ✓ 10 METERS DETACHABLE SCHUKO OR FUSED UK PLUG CORD-SET. 15 METERS ACTION RANGE.
- ✓ LIFT OFF WING SHAPED QUICK STORAGE CORDSET HOLDER.

MAX. MOTOR POWER : 1100W 50/60 hz
MAX. VACUUM POWER : 210 mbar
MAX. AIRFLOW : 45 L/Sec
NOISE LEVEL : 64 db



MEASUREMENTS : 39 x 34 x 42,5 CM (LxWxH). WEIGHT : 6 KG (APPLIANCE)

- ✓ EPA HOSE ASSEMBLY EXTENDING FULL 3 METERS !
- ✓ METAL BEND HANDLE C/W AIR REGULATOR, STEEL MINI EXTENSION TUBE SET AND WHEELED FLOOR/BRUSH TOOL FOR FLOORS, WALLS AND CEILINGS.
- ✓ CREVICE NOZZLE, FLEXIBLE RUBBER NOZZLE AND D-SHAPE BRUSH NOZZLE FOR DETAILED CLEANING.
- ✓ 12 L FILTERBAG CAPACITY. UNIT AVAILABLE IN TWO CLEANROOM ISO 14644-1 FILTER SET-UP'S.
- ✓ OVERSIZED MOTORFILTER ENSURES STEADY AIRFLOW EXTENDING BOTH MOTOR & FILTER LIFE. ELIMINATES PREMATURE CLOGGING.
- ✓ OPTIONAL BLOW ASSEMBLIES TURN UNIT INTO A VERY POWERFUL BLOWER. A GREAT ALTERNATIVE TO COMPRESSED OR COSTLY CANNED AIR (GAS DUSTERS).
- ✓ 100V & 120V VERSIONS AVAILABLE.



FILTER CONFIGURATIONS (FILTER SET-UP'S) AVAILABLE :

ISO 7 (CLASS 10.000)

GERMAN "M" CLASS MELTBLOWN FILTERBAG MT-850/MT-851 + HEPA H14 MOTORFILTER MT-853 + HEPA H14 MT-857 EXIT FILTER

ISO 4 (CLASS 10)

GERMAN "M" CLASS MELTBLOWN FILTERBAG MT-850/MT-851 + HEPA H14 MOTORFILTER MT-853 + ULPA U15 MT-858 EXIT FILTER

EPA/CR BlowVac Special Electronic (Silent version)

- ✓ ADDED NOISE ABSORBING MATERIALS.
- ✓ FULL ELECTRONIC STEPLESS CONTROL OF :
 - MOTOR SPEED
 - ELECTRIC CONSUMPTION
 - VACUUM POWER
 - BLOW POWER
 - NOISE LEVEL



MEASUREMENTS : 39 x 34 x 42,5 CM (LxWxH). WEIGHT : 6 KG (APPLIANCE)



MUNTZ 888-ESD-S-E GS